

## VISTA-10P

### VISTA® CONTROL PANEL



Honeywell's feature-rich VISTA-10P is the industry's most economical and versatile control panel and is ideally suited for a wide range of applications. The six-zone panel significantly reduces dealer training and service call costs thanks to user-friendly features that make operation easier than ever. VISTA-10P gives you the ability to send alarm signals and upload/download via an Internet Protocol (IP),

improving the speed at which information can be delivered to and from the control panel. In addition, when used with an AlarmNet® Internet or 4G communicator, the VISTA-10P can be installed in premises without TELCO lines. The VISTA-10P increases upsell opportunities through its expansion capabilities and flexibility.

## FEATURES

- IP alarm reporting and uploading/downloading capability for Internet and Intranet use via iGSMV4G, 7845i-ENT, GSMV4G or GSMX4G
- Six hardwired zones on board
- 16 wireless expansion zones totaling 22 protection zones
- Eight independent keyfob zones allow two wireless keys to be programmed without using any of the 22 zones
- 32 Event log
- 16 user codes
- One configurable zone type allows installers to create their own custom zone type
- Two on-board triggers
- Four output devices using a 4204 relay module
- Valuable End-user Features**
  - Flexible function keys allow single button arming
  - One programmable macro key
  - Viewable on system keypad display
    - Exit countdown
    - Time and date\*
    - Event log\*
  - Two schedules
    - Can activate relays on programmed times or on events
    - Latchkey reports to a pager
    - “User Access” time windows
- Chime by zone
- Four output devices with multiple actions per device
  - Turn lights on when system disarms with a 4204 Relay
  - Flash same lights when system is in alarm using a 4204 Relay
- Fully compatible with Honeywell Total Connect™ Remote Services

\*with Alpha Keypad

# VISTA-10P

## VISTA® CONTROL PANEL

### SPECIFICATIONS

#### Electrical

- Aux power 12VDC, 600mA max
- Seven hour standby at 400 mA aux load with four amp hour battery
- 16.5VAC/25VA transformer
- Alarm output 12VDC, 2.0A max
- For UL installations, combined aux and alarm output cannot exceed 700mA

#### Output Control

- Supports multiple output devices, one 4204 and two triggers

#### Zones

- Six hardwired zones
- Selectable response: 10msec, 350msec, 750msec
- 16 selectable zone types plus one configurable zone type
- Programmable swinger suppression

#### Expansion Devices

- 4204 – Up to four relays – 15mA standby (each active relay draws an additional 40mA)

#### Accessories

- iGSMV4G Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator

- GSMV4G Digital Cellular Communicator with Remote Service Capability
- GSMX4G Digital Cellular Communicator for VISTA Control Panels
- 5881ENL RF Receiver supports up to eight zones – 60mA
- 5881ENM supports up to 16 zones – 60mA
- 5881ENH supports up to 48 zones – 60mA
- 5883 Transceiver supports up to 40 zones – 80mA

#### Keypads

- 6162 Custom Alpha Security Keypad – 40mA/120mA
- 6162V Voice Custom Alpha Security Keypad – 60mA/190mA
- 6162RF Custom Alpha Receiver/Security Keypad – 120mA/210mA
- 6152 Fixed-English Security Keypad – 40mA/70mA
- 6152V Voice Fixed-English Security Keypad – 60mA/190mA
- 6152RF/6152RFFR Fixed-English/French Receiver/Security Keypad – 80mA/105mA
- 6152ZN/6152ZNFR Fixed-English/French Security Keypad with Hardwired Zone – 35mA/80mA
- 6148 Fixed English LCD – 30mA/55mA

#### Agency Listings

##### ETL listing

- Residential Fire and Burglary:
  - Household Fire Warning System Units – ANSI/UL 985, 2000/05/26 (5th edition) with revisions up to 2004/04/29

#### Smoke Detectors

- Supports four-wire smoke detectors

#### Communications

- iGSMV4G Internet and Digital Cellular Communicator with Remote Service Capability
- 7845i-ENT Enterprise Internet Communicator
- GSMV4G Digital Cellular Communicator with Remote Service Capability
- GSMX4G Digital Cellular Communicator for VISTA Control Panels
- Touchtone or pulse
- Formats supported
  - ADEMCO® Contact ID
  - ADEMCO 4 + 2 Express
  - ADEMCO low speed
  - Sescoa/Radionics
- 3 + 1, 4 + 1 and 4 + 2 reporting
- Reporting capabilities
  - Split
  - Dual
  - Split/Dual – True dial tone detection
- Low battery reports 11.2 – 11.6VDC
- AC loss and restoral reporting supported

### ORDERING

<b>VISTA-10P</b>	Control Panel
<b>VISTA-10PSIA</b>	Control Panel for CP-01 SIA certifications

#### Automation and Control Solutions

Honeywell Security Products Americas  
2 Corporate Center Dr. Suite 100  
P.O. Box 9040  
Melville, NY 11747  
1.800.467.5875  
www.honeywell.com

L/VISTA10PD/D  
December 2013  
© 2013 Honeywell International Inc.

# Honeywell